

PRODUCT MODEL



700S LED



700E LED



HF-280LED



HF-280ELED



HF-280CLED



HF-280WLED



500S LED



500E LED

700 500 280 LED SERIES TECHNICAL DATA

Type	Illuminance	Colour temperature	Colour reduction index(Ra)	Total irradiance	Size of light field	Service life of illuminant	Power supply voltage	Brightness adjustment	Total power consumption	Total LED bulb quantity	Emergency time	ENDO
700S LED	≥160,000Lux	3800±500K 4400±500K 5000±500K	93	544W/m <sup>2</sup>	250~300mm	50,000h	AC110-240V 50/60Hz	Automatic8-stage continuous light adjustment	80W	108pcs (18*6)	/	YES
700E LED	≥160,000Lux	3800±500K 4400±500K 5000±500K	93	544W/m <sup>2</sup>	250~300mm	50,000h	AC110-240V 50/60Hz	Automatic8-stage continuous light adjustment	80W	108pcs (18*6)	≥6 hours	YES
500S LED	≥140,000Lux	3800±500K 4400±500K 5000±500K	93	534W/m <sup>2</sup>	250~300mm	50,000h	AC110-240V 50/60Hz	Automatic8-stage continuous light adjustment	60W	72pcs (12*6)	/	YES
500E LED	≥140,000Lux	3800±500K 4400±500K 5000±500K	93	534W/m <sup>2</sup>	250~300mm	50,000h	AC110-240V 50/60Hz	Automatic8-stage continuous light adjustment	60W	72pcs (12*6)	≥6 hours	YES
HF-280LED	≥50,000Lux	4000±500K	97	171W/m <sup>2</sup>	150mm	50,000h	AC110-240V 50/60Hz	/	20W	19pcs	/	
HF-280ELED	≥50,000Lux	4000±500K	97	171W/m <sup>2</sup>	150mm	50,000h	AC110-240V 50/60Hz	/	20W	19pcs	≥2 hours	
HF-280CLED	≥50,000Lux	4000±500K	97	171W/m <sup>2</sup>	150mm	50,000h	AC110-240V 50/60Hz	/	20W	19pcs	/	
HF-280WLED	≥50,000Lux	4000±500K	97	171W/m <sup>2</sup>	150mm	50,000h	AC110-240V 50/60Hz	/	20W	19pcs	/	