



Dry/Incubator (Dual-purpose)

PPH-050A

- ◆ Microprocessor control, oven/incubator hierarchical control
- ◆ With double glass window
- ◆ Digital display setting and actual temperature
- ◆ Digital display running timer
- ◆ Stainless-steel interior, chamber corners are semicircle

Safety Mechanism:

- ◆ PID self-tuning, over temperature alarm
- ◆ Automatic alarm after operation

Ideal For:

- ◆ The hot air circulation system is composed of low-noise fans and suitable air ducts, and the temperature in the box is uniform.

Scope of application:

- ◆ This product is suitable for drying, baking, wax melting, sterilization, and curing in industrial and mining enterprises, medical and health care, and scientific research institutions. It can also be used for bacterial culture, breeding, fermentation and other constant temperature tests.



PPH-030A

Model	PPH-030A	PPH-050A	PPH-070A	PPH-140A	PPH-240A
Capacity	40L	50L	70L	140L	225L
Working size(mm)	350x350x350	415x375x345	450x350x450	550x450x550	500x600x750
Power	850W	850W	1100W	1600W	2100W
Temperature range	As incubator: RT+5~80℃, As oven 80~250℃				
Temperature resolution	0.1℃				
Temperature fluctuation	As incubator: ±0.5℃, As oven: ±1℃				
Timer	0-9999min				
Voltage	110V 60Hz /220V 50Hz				
Dimension(mm)	620x630x520	690x610x530	620x710x620	720x780x750	770x840x980
Package(mm)	700x710x620	790x660x620	720x780x730	830x880x860	940x870x1140
G.W./N.W.	54/38kg	58/45kg	64/56kg	88/72kg	116/90kg

Vacuum Dry Oven

DZF-6020/6050 DZF-6090/6210(floor) DZF-6020DP/6050DP DZF-6090DP/6210DP(floor)

- ◆ Microprocessor control,
- ◆ With glass window door
- ◆ Digital display setting and actual temperature
- ◆ Digital display running timer
- ◆ PID self-tuning, over temperature alarm
- ◆ Automatic alarm after operation
- ◆ DZF-6020DP series with digital control vacuum display

Scope of application:

- ◆ Suitable for drying, baking, dewaxing, sterilization, heat treatment under vacuum conditions



DZF-6020

DZF-6050DP

DZF-6210

Model	DZF-6020	DZF-6050	DZF-6090	DZF-6210
Capacity	25L	50L	90L	210L
Working size(mm)	300x300x275	415x375x345	450x450x450	560x640x600
Power	1000W	1400W	1600W	2160W
Vacuum pump	Without	Without	Yes	Yes
Temperature range	50~180℃	50~200℃	50~250℃	50~250℃
Temperature fluctuation	±1%			
Vacuum degree	<133Pa			
Timer	0-999min			
Voltage	220V 50Hz			
Dimension(mm)	570x460x460	710x540x550	610x670x1430	810x720x1590
Package(mm)	670x540x570	810x620x650	750x740x1580	890x840x1680
G.W./N.W.	54/42kg	76/60kg	163/117kg	195/140kg