



Table Top Steam Sterilizer

Use

The table type sterilizers are safely auto-controlled, which are designed for the dental clinics, hospitals, school lab, scientific research institutions and laboratory. And mostly suitable for sterilizing of surgical, dental and eye instruments, glassware medicine, culture medium and biological dressing, food, etc.

Characteristics

- ◆ For 4~6 minutes rapidly sterilizing.
- ◆ Digital display of working status, touch type key.
- ◆ With 3 fixed cycles of sterilizing program and adjustable for user.
- ◆ The whole process of water adding, temperature rising, sterilizing, drying steam discharging controlled automatically.
- ◆ Steam-water inner circulation system: no steam discharge, and the environment for sterilizing will be clean and dry.
- ◆ Safe protection of water lacking.
- ◆ Exhaust the cool air automatically.
- ◆ Door safety lock system.
- ◆ With four stainless steel sterilizing plates.
- ◆ The chamber of the sterilizer is made of stainless steel.
- ◆ Automatically shut off with beep reminding after sterilization.
- ◆ With drying function.



Technical Data

MODEL	TM-XD20D	TM-XD24D
Technical Data		
Sterilizing chamber volume	20L φ 250 × 420mm	24L φ 250 × 520mm
Working pressure	0.22MPa	
Working temperature	134°C	
Temperature adjust range	105~134°C	
Timer range	0~99min	
Heat average	≤ ± 1°C	
Power	1.5KW / AC220V, 50Hz	
Sterilizing plate(mm)	340 × 200 × 30(3piece)	400 × 200 × 30(3piece)
Dimension(mm)	480 × 680 × 455	480 × 680 × 455
Exterior package dimension(mm)	580 × 700 × 500	580 × 800 × 560
G.W/N.W	43kg / 40kg	50kg / 45kg

